

FLOOR HEATING INSTALLATION

ETHERMA PTX - Thermal feet mat



USE

Thermal feet mats for floor laying are wheelchair-resistant, robust and have a diamond-pattern covering. Suitable for indoor use such as at work stations, work benches, points of sale, despatch points, containers, etc. The mats are completely waterproof and can therefore also be used in humid environments.

The heavy-duty version, PTXS-2, provides higher performance, and this heating mat can be used wherever demands on the mat will be greater.

LAYING INSTRUCTIONS

The heating mats can also be screwed to the floor laid in a modular manner on the short side.

Width: 60 cm Length: 90 cm

The groove profile on the underside of the heating mat provides the necessary insulation. We recommend additional insulation at particularly low floor temperatures (< 0 °C).

Suitable for milking stands as the product is acid and lactic acid-resistant.



NEW
EXECUTION IN
QUALITY RUBBER

TECHNICAL DATA



- > Voltage: 230 V
- > Surface temperature: 25 – 35 °C
- > Surface: Diamond pattern
- > Material: Rubber
- > Colour: Black
- > Strength: 14 mm
- > Protection rating: IP X7
- > Protection class: I
- > Cable: 2 m with plug
- > Approval: CE compliant
- > Weight: 8.9 kg

BENEFITS OF THIS PRODUCT

- + Ergonomic foot mat
- + High level of safety thank to temperature limiter
- + Highly elastic, resistant to foot traffic, anti-slip
- + Simple to clean
- + Waterproof
- + Fire-retardant B1
- + Acid and lactic acid-resistant

SELECTION GUIDE

- PTX-2: For indoor use at normal floor temperatures.
- PTXS-2: For use in Christmas markets, containers and other outdoor use.

Thermal feet mat, 230 V, IP X7

RG: 021 | DT: ex stock

Type	Order no.	Output (W)	Voltage (V)	Dimensions (cm)	
				Length	Width
PTX-2	40045	100	230	90	60
PTXS-2	40046	170	230	90	60